



Uniclass L725111	EPIC G611
CI/SFB (74.26)	X

DATA

Thermostatic & Pressure Balanced Mixing Valve
 Exposed Supply. No Wall Fixing Plate Required
 Maximum Temperature 90°
 Minimum Pressure 1.0 Bar
 Maximum Pressure 16.0 Bar
 Pressure Differential 10.0 Bar
 Normal Control Temperature 38°
 Output Temp Differential +/- 1°c
 Max Output 12 l/pm @ 3 Bar

MATERIALS

Mixer Body BZR Brass With Chrome Finish
 Riser BZR Brass With Chrome Finish
 c/w ABS plastic fittings
 Handles ABS Plastic
 Hose Double interlock Large Bore Chrome
 Connections Inlet Valve Body G1/2 BSP

COLOUR

Frost

FEATURES

Thermostatic & Pressure Balanced Cartridges constant temp
 regardless of pressure variations
 Anti Scald cut off 0.02 seconds
 No wall Fixing Plate required
 Luxury Riser Kit
 Multi Function Showerhead
 Quick & Easy to fit & maintain
 NRV Fitted to Hot & Cold Inlets
 We recommend the use of isolating ball valves with our units

SPEC CODES

Exposed Supply 9250LUX

Special Offer While Stocks Last

9250 Luxury Mixer Kit



10 YEAR CALCIUM GUARANTEE	10 YEAR PRESSURE GUARANTEE	10 YEAR TEMPERATURE GUARANTEE
FM Mattsson	FM Mattsson	FM Mattsson

